

Specialty Doors



Clear-Way Strip Door

- ❖ Saves Energy by Minimizing Air Loss
- ❖ Available in Standard Smooth, Ribbed, Cool Temp, Anti-Static, Safety Orange, Anti-Insect Yellow, Opaque Black, Screen Flex (Red, Green, and Bronze)
- ❖ Prevents Movement of Dust and Other Contaminants from One Area to Another

Security Gate



- ❖ Provides Ability to Control Access
- ❖ Custom Built Solutions Suit Any Opening
- ❖ Provides Around the Clock Security (Locking Bars Included)
- ❖ Center Lock (Split Gate) Standard, (Single Open Gate Available)

Air Curtain



- ❖ Provides a Thermal Barrier that Separates One Environment From Another
- ❖ Promotes Safety, By Providing an Unobstructed View of Doorways
- ❖ Widths Ranging from 2.5' to 30' and Heights Up to 30'

Pioneer Industrial Doors



RollRight 200

- ❖ Opening Speeds up to 22" Per Second
- ❖ Maximum Door Size 25' W x 20'H
- ❖ Available in Spring Assist, Chain Hoist, Intube, and 22" Jack Shaft Operator
- ❖ Fiberglass Windbars Remain Flexible Enough to Pop Out in case of Accidental Contact
- ❖ Automatically Resets After Impact
- ❖ Available in 22 oz. and 40 oz. Vinyl (40 oz. Available in Select Colors)
- ❖ Aluminum Hinge Available for Additional Wind Load



NoPest Doors

- ❖ 11 oz. Vinyl Coated Mesh Polyester Screen
- ❖ Available in Spring Assist, Chain Hoist, Sliding or Motorized. Up to 36" Per Second Opening Speed
- ❖ Standard Sizes Up to 16'W x 18'H
- ❖ Horizontal Stiffeners Bend if Loaded - Will Not Break or Kink
- ❖ Double Baffle Valance (at Top), EPDM Seals on Both Sides, Prevent Pest Intrusion
- ❖ Helps Meet FDA Requirements



RollRight 300



* Wind Load Varies by Door Size

- ❖ Opening Speeds up to 36" Per Second
- ❖ Wind Loads up to 45 mph *
- ❖ Also Available in HG Model for Extreme Conditions
- ❖ Exchangeable Panels Available for Multi-Seasonal Use
- ❖ Fiberglass Windbars Won't Bend or Break
- ❖ Automatically Resets After Impact
- ❖ Standard Sizes Up to 16'W x 16'H
- ❖ Low Maintenance - No Cables, Wheels, Springs, or Sewn Construction

SealTight Doors

- ❖ Standard Sizes Up to 24' W x 22'H *
- ❖ 400ST - Manaras Operator with opening Speeds 8" to 10" Per Second
- ❖ 500ST/600ST - Fully Programmable Smart Controller with Direct Drive Motor, Can Reach Speeds Up to 48" Per Second *
- ❖ Unique 100% Sealing System
- ❖ Larger Size Available up to 30'W x 30'H (850ST)
- ❖ Lightweight, Easy to Clean, Corrosion Resistant Aluminum Frame



*Opening Speeds Vary by Door Size

RollRight 400

- ❖ Opening Speeds up to 52" Per Second
- ❖ 45 mph Wind Load Rated*
- ❖ Exchangeable Panels Available for Multi-Seasonal Use
- ❖ Meets NFPA-701 & CSFM Standards for Flame Retardancy
- ❖ Fully Programmable Smart Control Panel
- ❖ Fiberglass Windbars (Won't Bend or Break)
- ❖ True 1 hp. Direct Drive Motor
- ❖ Fabric Resistant to Tearing, Ultraviolet Rays, Rot, and Mildew



* Wind Load Varies by Door Size

Freezer Door

- ❖ Digitally Controlled Condensation Management System (CMS)
- ❖ Smart 50 Microprocessor Controller, Digital Encoder
- ❖ R-4 Insulation Value
- ❖ Opening Speeds up to 48"/Second

